VERSITILE HOME INSPECTION 404-787-8222 bell11201@msn.com https://www.wewillinspect.com





RESIDENTIAL REPORT

315 Sunflower Ln Covington, GA 30016

Keith Bell JUNE 29, 2024



Inspector Clemet Bell InterNACHI Certified - Next Insured 404-787-8222 bell11201@msn.com

TABLE OF CONTENTS

1: Inspection Details	4
2: Roof	5
3: Exterior	7
4: Basement, Foundation, Crawlspace & Structure	9
5: Heating	10
6: Cooling	11
7: Plumbing	13
8: Electrical	15
9: Fireplace	16
10: Attic, Insulation & Ventilation	17
11: Doors, Windows & Interior	18
12: Built-in Appliances	23
Standards of Practice	25

SUMMARY



- 3.1.1 Exterior Siding, Flashing & Trim: Mildew/Algae
- ⊖ 3.2.1 Exterior Exterior Doors: Defective Weather Stripping
- ⊖ 3.3.1 Exterior Walkways, Patios & Driveways: Driveway Cracking Minor
- O 3.3.2 Exterior Walkways, Patios & Driveways: Patio Cracking Minor
- 3.4.1 Exterior Decks, Balconies, Porches & Steps: Cracks in Concrete Front Porch
- ⊖ 3.6.1 Exterior Vegetation, Grading, Drainage & Retaining Walls: Negative Grading
- ⊖ 6.1.1 Cooling Cooling Equipment: Unusually Noisy
- 7.7.1 Plumbing Water Meter: Water Meter Top is missing
- 🕒 11.1.1 Doors, Windows & Interior Doors: Lock on lower part of door is hazardous
- ⊖ 11.2.1 Doors, Windows & Interior Windows: Damaged
- 🕒 11.2.2 Doors, Windows & Interior Windows: Failed Seal
- ⊖ 11.3.1 Doors, Windows & Interior Floors: Missing Transition
- 🕒 11.6.1 Doors, Windows & Interior Steps, Stairways & Railings: Loose Handrail

1: INSPECTION DETAILS

Information

In Attendance Client, Home Owner

Temperature (approximate) 75 Fahrenheit (F) **Occupancy** Furnished, Occupied

Type of Building Single Family **Style** Multi-level

Weather Conditions Light Rain

2: ROOF

Information

Roof Type/Style Gable

Coverings: Material Asphalt Roof Drainage Systems: Gutter Material Seamless Aluminum



Flashings: Material

Vinyl



Inspection Method Ground



3: EXTERIOR

Siding, Flashing & Trim: Siding

Walkways, Patios & Driveways:

Material

Vinyl, Brick

Concrete

Driveway Material

Information

Inspection Method Attic Access, Visual

Exterior Doors: Exterior Entry Door Steel

Decks, Balconies, Porches & Steps: Material Concrete

Deficiencies

3.1.1 Siding, Flashing & Trim

MILDEW/ALGAE

RIGHT SIDE OF HOUSE

There are signs of algae and/or mildew on the siding. This is a cosmetic issue and is not uncommon especially on shaded portions of the home. Recommend that said areas be washed or cleaned or a regular basis.

3.2.1 Exterior Doors

DEFECTIVE WEATHER STRIPPING

Recommendation Contact a qualified professional.

3.3.1 Walkways, Patios & Driveways

DRIVEWAY CRACKING - MINOR

Minor cosmetic cracks observed, which may indicate movement in the soil. Recommend monitor and/or have concrete contractor patch/seal.

3.3.2 Walkways, Patios & Driveways

PATIO CRACKING - MINOR

Normal settling & cracking observed. Recommend monitor and/or patch/seal.



Decks, Balconies, Porches & Steps: Appurtenance Front Porch



Maintenance Item

3.4.1 Decks, Balconies, Porches & Steps **CRACKS IN CONCRETE - FRONT PORCH** Recommendation **Contact a qualified professional.**

3.6.1 Vegetation, Grading, Drainage & Retaining Walls

NEGATIVE GRADING

BACKYARD

Grading is sloping towards the home in some areas. This could lead to water intrusion and foundation issues. Recommend qualified landscaper or foundation contractor regrade so water flows away from home.

Here is a helpful article discussing negative grading.



Maintenance Item

4: BASEMENT, FOUNDATION, CRAWLSPACE & STRUCTURE

Information

Inspection Method

Visual

Foundation: Material Slab on Grade

5: HEATING

6: COOLING

Information

Cooling Equipment: Brand Gibson



Cooling Equipment: Energy Source/Type

Heat Pump, Electric, Central Air Conditioner, Window AC, Ceiling Fan **Cooling Equipment: Location** Exterior West

Distribution System: Configuration Central

Deficiencies

6.1.1 Cooling Equipment

UNUSUALLY NOISY



Compressor started and operated but unit was unusually noisy. Recommend licensed HVAC contractor evaluate.



7: PLUMBING

Information

Filters

None

Water Source Public



Deficiencies

7.7.1 Water Meter **WATER METER TOP IS MISSING** Recommendation **Contact a qualified professional.**







8: ELECTRICAL

Information

Service Entrance Conductors:

Electrical Service Conductors Below Ground, 120 Volts, 220 Volts

9: FIREPLACE

10: ATTIC, INSULATION & VENTILATION

11: DOORS, WINDOWS & INTERIOR

Information

Windows: Window Manufacturer Windows: Window Type Unknown

Double-hung

Walls: Wall Material Drywall



Ceilings: Ceiling Material Plaster



Countertops & Cabinets: Cabinetry Laminate Countertops & Cabinets: Countertop Material Laminate



Floors: Floor Coverings Carpet, Vinyl



Limitations

HVAC IN WINDOW



Deficiencies

11.1.1 Doors **LOCK ON LOWER PART OF DOOR IS HAZARDOUS**Recommendation

Contact a qualified professional.



Kitchen

11.2.1 Windows

DAMAGED

One or more windows appears to have general damage, but are operational. Recommend a window professional clean, lubricate & adjust as necessary.



11.2.2 Windows

FAILED SEAL

Observed condensation between the window panes, which indicates a failed seal. Recommend qualified window contractor evaluate & replace.



Guest Bedroom - Upstairs Front Left



11.3.1 Floors **MISSING TRANSITION** Recommendation **Contact a qualified professional.**



Keith Bell



Hallway to Office

Foyer to Dining Room

11.6.1 Steps, Stairways & Railings **LOOSE HANDRAIL** Recommendation **Contact a qualified professional.**





12: BUILT-IN APPLIANCES

Information

Range/Oven/Cooktop: Exhaust Hood Type None Range/Oven/Cooktop: Range/Oven Brand Hotpoint



Range/Oven/Cooktop: Range/Oven Energy Source Electric

Dishwasher: Brand

HotPoint



Dishwasher in kitchen

Refrigerator: Brand Frigidaire



STANDARDS OF PRACTICE

Roof

I. The inspector shall inspect from ground level or the eaves: A. the roof-covering materials; B. the gutters; C. the downspouts; D. the vents, flashing, skylights, chimney, and other roof penetrations; and E. the general structure of the roof from the readily accessible panels, doors or stairs. II. The inspector shall describe: A. the type of roof-covering materials. III. The inspector shall report as in need of correction: A. observed indications of active roof leaks. IV. The inspector is not required to: A. walk on any roof surface. B. predict the service life expectancy. C. inspect underground downspout diverter drainage pipes. D. remove snow, ice, debris or other conditions that prohibit the observation of the roof surfaces. E. move insulation. F. inspect antennae, satellite dishes, lightning arresters, de-icing equipment, or similar attachments. G. walk on any roof areas that appear, in the inspectors opinion, to be unsafe. H. walk on any roof areas if doing so might, in the inspector's opinion, cause damage. I. perform a water test. J. warrant or certify the roof. K. confirm proper fastening or installation of any roof-covering material.

Exterior

I. The inspector shall inspect: A. the exterior wall-covering materials, flashing and trim; B. all exterior doors; C. adjacent walkways and driveways; D. stairs, steps, stoops, stairways and ramps; E. porches, patios, decks, balconies and carports; F. railings, guards and handrails; G. the eaves, soffits and fascia; H. a representative number of windows; and I. vegetation, surface drainage, retaining walls and grading of the property, where they may adversely affect the structure due to moisture intrusion. II. The inspector shall describe: A. the type of exterior wall-covering materials. III. The inspector shall report as in need of correction: A. any improper spacing between intermediate balusters, spindles and rails. IV. The inspector is not required to: A. inspect or operate screens, storm windows, shutters, awnings, fences, outbuildings, or exterior accent lighting. B. inspect items that are not visible or readily accessible from the ground, including window and door flashing. C. inspect or identify geological, geotechnical, hydrological or soil conditions. D. inspect recreational facilities or playground equipment. E. inspect seawalls, breakwalls or docks. F. inspect erosion-control or earth-stabilization measures. G. inspect for safety-type glass. H. inspect underground utilities. I. inspect underground items. J. inspect wells or springs. K. inspect solar, wind or geothermal systems. L. inspect swimming pools or spas. M. inspect drainfields or dry wells. P. determine the integrity of multiple-pane window glazing or thermal window seals.

Basement, Foundation, Crawlspace & Structure

I. The inspector shall inspect: A. the foundation; B. the basement; C. the crawlspace; and D. structural components. II. The inspector shall describe: A. the type of foundation; and B. the location of the access to the under-floor space. III. The inspector shall report as in need of correction: A. observed indications of wood in contact with or near soil; B. observed indications of active water penetration; C. observed indications of possible foundation movement, such as sheetrock cracks, brick cracks, out-of-square door frames, and unlevel floors; and D. any observed cutting, notching and boring of framing members that may, in the inspector's opinion, present a structural or safety concern. IV. The inspector is not required to: A. enter any crawlspace that is not readily accessible, or where entry could cause damage or pose a hazard to him/herself. B. move stored items or debris. C. operate sump pumps with inaccessible floats. D. identify the size, spacing, span or location or determine the adequacy of foundation bolting, bracing, joists, joist spans or support systems. E. provide any engineering or architectural service. F. report on the adequacy of any structural system or component.

Heating

I. The inspector shall inspect: A. the heating system, using normal operating controls. II. The inspector shall describe: A. the location of the thermostat for the heating system; B. the energy source; and C. the heating method. III. The inspector shall report as in need of correction: A. any heating system that did not operate; and B. if the heating system was deemed inaccessible. IV. The inspector is not required to: A. inspect or evaluate the interior of flues or chimneys, fire chambers, heat exchangers, combustion air systems, fresh-air intakes, humidifiers, dehumidifiers, electronic air filters, geothermal systems, or solar heating systems. B. inspect fuel tanks or underground or concealed fuel supply systems. C. determine the uniformity, temperature, flow, balance, distribution, size, capacity, BTU, or supply adequacy of the heating system. D. light or ignite pilot flames. E. activate heating, heat pump systems, or other heating systems when ambient temperatures or other circumstances are not conducive to safe operation or may damage the equipment. F. override electronic thermostats. G. evaluate fuel quality. H. verify thermostat calibration, heat anticipation, or automatic setbacks, timers, programs or clocks.

Cooling

I. The inspector shall inspect: A. the cooling system, using normal operating controls. II. The inspector shall describe: A. the location of the thermostat for the cooling system; and B. the cooling method. III. The inspector shall report as in need of correction: A. any cooling system that did not operate; and B. if the cooling system was deemed inaccessible. IV. The inspector is not required to: A. determine the uniformity, temperature, flow, balance, distribution, size, capacity, BTU, or supply adequacy of the cooling system. B. inspect portable window units, through-wall units, or electronic air filters. C. operate equipment or systems if the exterior temperature is below 65 Fahrenheit, or when other circumstances are not

conducive to safe operation or may damage the equipment. D. inspect or determine thermostat calibration, cooling anticipation, or automatic setbacks or clocks. E. examine electrical current, coolant fluids or gases, or coolant leakage.

Plumbing

I. The inspector shall inspect: A. the main water supply shut-off valve; B. the main fuel supply shut-off valve; C. the water heating equipment, including the energy source, venting connections, temperature/pressure-relief (TPR) valves, Watts 210 valves, and seismic bracing; D. interior water supply, including all fixtures and faucets, by running the water; E. all toilets for proper operation by flushing; F. all sinks, tubs and showers for functional drainage; G. the drain, waste and vent system; and H. drainage sump pumps with accessible floats. II. The inspector shall describe: A. whether the water supply is public or private based upon observed evidence; B. the location of the main water supply shut-off valve; C. the location of the main fuel supply shut-off valve; D. the location of any observed fuel-storage system; and E. the capacity of the water heating equipment, if labeled. III. The inspector shall report as in need of correction: A. deficiencies in the water supply by viewing the functional flow in two fixtures operated simultaneously; B. deficiencies in the installation of hot and cold water faucets; C. mechanical drain stops that were missing or did not operate if installed in sinks, lavatories and tubs; and D. toilets that were damaged, had loose connections to the floor, were leaking, or had tank components that did not operate. IV. The inspector is not required to: A. light or ignite pilot flames. B. measure the capacity, temperature, age, life expectancy or adequacy of the water heater. C. inspect the interior of flues or chimneys, combustion air systems, water softener or filtering systems, well pumps or tanks, safety or shut-off valves, floor drains, lawn sprinkler systems, or fire sprinkler systems. D. determine the exact flow rate, volume, pressure, temperature or adequacy of the water supply. E. determine the water quality, potability or reliability of the water supply or source. F. open sealed plumbing access panels. G. inspect clothes washing machines or their connections. H. operate any valve. I. test shower pans, tub and shower surrounds or enclosures for leakage or functional overflow protection. J. evaluate the compliance with conservation, energy or building standards, or the proper design or sizing of any water, waste or venting components, fixtures or piping. K. determine the effectiveness of anti-siphon, backflow prevention or drain-stop devices. L. determine whether there are sufficient cleanouts for effective cleaning of drains. M. evaluate fuel storage tanks or supply systems. N. inspect wastewater treatment systems. O. inspect water treatment systems or water filters. P. inspect water storage tanks, pressure pumps, or bladder tanks. Q. evaluate wait time to obtain hot water at fixtures, or perform testing of any kind to water heater elements. R. evaluate or determine the adequacy of combustion air. S. test, operate, open or close: safety controls, manual stop valves, temperature/pressure-relief valves, control valves, or check valves. T. examine ancillary or auxiliary systems or components, such as, but not limited to, those related to solar water heating and hot water circulation. U. determine the existence or condition of polybutylene plumbing. V. inspect or test for gas or fuel leaks, or indications thereof.

Electrical

I. The inspector shall inspect: A. the service drop; B. the overhead service conductors and attachment point; C. the service head, gooseneck and drip loops; D. the service mast, service conduit and raceway; E. the electric meter and base; F. service-entrance conductors; G. the main service disconnect; H. panelboards and over-current protection devices (circuit breakers and fuses); I. service grounding and bonding; J. a representative number of switches, lighting fixtures and receptacles, including receptacles observed and deemed to be arc-fault circuit interrupter (AFCI)-protected using the AFCI test button, where possible; K. all ground-fault circuit interrupter receptacles and circuit breakers observed and deemed to be GFCIs using a GFCI tester, where possible; and L. smoke and carbon-monoxide detectors. II. The inspector shall describe: A. the main service disconnect's amperage rating, if labeled; and B. the type of wiring observed. III. The inspector shall report as in need of correction: A. deficiencies in the integrity of the serviceentrance conductors insulation, drip loop, and vertical clearances from grade and roofs; B. any unused circuit-breaker panel opening that was not filled; C. the presence of solid conductor aluminum branch-circuit wiring, if readily visible; D. any tested receptacle in which power was not present, polarity was incorrect, the cover was not in place, the GFCI devices were not properly installed or did not operate properly, evidence of arcing or excessive heat, and where the receptacle was not grounded or was not secured to the wall; and E. the absence of smoke detectors. IV. The inspector is not required to: A. insert any tool, probe or device into the main panelboard, sub-panels, distribution panelboards, or electrical fixtures. B. operate electrical systems that are shut down. C. remove panelboard cabinet covers or dead fronts. D. operate or re-set over-current protection devices or overload devices. E. operate or test smoke or carbon-monoxide detectors or alarms F. inspect, operate or test any security, fire or alarms systems or components, or other warning or signaling systems. G. measure or determine the amperage or voltage of the main service equipment, if not visibly labeled. H. inspect ancillary wiring or remote-control devices. I. activate any electrical systems or branch circuits that are not energized. J. inspect low-voltage systems, electrical de-icing tapes, swimming pool wiring, or any timecontrolled devices. K. verify the service ground. L. inspect private or emergency electrical supply sources, including, but not limited to: generators, windmills, photovoltaic solar collectors, or battery or electrical storage facility. M. inspect spark or lightning arrestors. N. inspect or test de-icing equipment. O. conduct voltage-drop calculations. P. determine the accuracy of labeling. Q. inspect exterior lighting.

Fireplace

I. The inspector shall inspect: readily accessible and visible portions of the fireplaces and chimneys; lintels above the fireplace openings; damper doors by opening and closing them, if readily accessible and manually operable; and cleanout doors and frames.

II. The inspector shall describe: the type of fireplace.

III. The inspector shall report as in need of correction: evidence of joint separation, damage or deterioration of the hearth, hearth extension or chambers; manually operated dampers that did not open and close; the lack of a smoke detector in the same room as the fireplace; the lack of a carbon-monoxide detector in the same room as the fireplace; and cleanouts not made of metal, pre-cast cement, or other non-combustible material.

IV. The inspector is not required to: inspect the flue or vent system. inspect the interior of chimneys or flues, fire doors or screens, seals or gaskets, or mantels. Determine the need for a chimney sweep, perate gas fireplace inserts, light pilot flames, determine the appropriateness of any installation, inspect automatic fuel-fed devices, inspect combustion and/or make-up air devices, inspect heat-distribution assists, whether gravity-controlled or fan-assisted, ignite or extinguish fires, determine the adequacy of drafts or draft characteristics, move fireplace inserts, stoves or firebox contents, perform a smoke test, dismantle or remove any component, perform a National Fire Protection Association (NFPA)-style inspection perform a Phase I fireplace and chimney inspection.

Attic, Insulation & Ventilation

I. The inspector shall inspect: A. insulation in unfinished spaces, including attics, crawlspaces and foundation areas; B. ventilation of unfinished spaces, including attics, crawlspaces and foundation areas; and C. mechanical exhaust systems in the kitchen, bathrooms and laundry area. II. The inspector shall describe: A. the type of insulation observed; and B. the approximate average depth of insulation observed at the unfinished attic floor area or roof structure. III. The inspector shall report as in need of correction: A. the general absence of insulation or ventilation in unfinished spaces. IV. The inspector is not required to: A. enter the attic or any unfinished spaces that are not readily accessible, or where entry could cause damage or, in the inspector's opinion, pose a safety hazard. B. move, touch or disturb insulation. C. move, touch or disturb vapor retarders. D. break or otherwise damage the surface finish or weather seal on or around access panels or covers. E. identify the composition or R-value of insulation material. F. activate thermostatically operated fans. G. determine the types of materials used in insulation or wrapping of pipes, ducts, jackets, boilers or wiring. H. determine the adequacy of ventilation.

Doors, Windows & Interior

I. The inspector shall inspect: A. a representative number of doors and windows by opening and closing them; B. floors, walls and ceilings; C. stairs, steps, landings, stairways and ramps; D. railings, guards and handrails; and E. garage vehicle doors and the operation of garage vehicle door openers, using normal operating controls. II. The inspector shall describe: A. a garage vehicle door as manually-operated or installed with a garage door opener. III. The inspector shall report as in need of correction: A. improper spacing between intermediate balusters, spindles and rails for steps, stairways, guards and railings; B. photo-electric safety sensors that did not operate properly; and C. any window that was obviously fogged or displayed other evidence of broken seals. IV. The inspector is not required to: A. inspect paint, wallpaper, window treatments or finish treatments. B. inspect floor coverings or carpeting. C. inspect central vacuum systems. D. inspect for safety glazing. E. inspect security systems or components. F. evaluate the fastening of islands, countertops, cabinets, sink tops or fixtures. G. move furniture, stored items, or any coverings, such as carpets or rugs, in order to inspect the concealed floor structure. H. move suspended-ceiling tiles. I. inspect or move any household appliances. J. inspect or operate equipment housed in the garage, except as otherwise noted. K. verify or certify the proper operation of any pressure-activated auto-reverse or related safety feature of a garage door. L. operate or evaluate any security bar release and opening mechanisms, whether interior or exterior, including their compliance with local, state or federal standards. M. operate any system, appliance or component that requires the use of special keys, codes, combinations or devices. N. operate or evaluate self-cleaning oven cycles, tilt guards/latches, or signal lights. O. inspect microwave ovens or test leakage from microwave ovens. P. operate or examine any sauna, steamgenerating equipment, kiln, toaster, ice maker, coffee maker, can opener, bread warmer, blender, instant hot-water dispenser, or other small, ancillary appliances or devices. Q. inspect elevators. R. inspect remote controls. S. inspect appliances. T. inspect items not permanently installed. U. discover firewall compromises. V. inspect pools, spas or fountains. W. determine the adequacy of whirlpool or spa jets, water force, or bubble effects. X. determine the structural integrity or leakage of pools or spas.