



PREMIUM HOSES

**HOW CAN WE
HELP YOU?**



MUD HOSE

Hose serves as a flexible connection between top of standpipe and swivel on offshore and onshore drilling and exploration. Also, serves as vibration reduction between mud pump and manifold.



CEMENT HOSE

Used in offshore and onshore drilling and work over cementing services. Flexible connection between cement pump and top drive for delivery of high-pressure cement.



UNBALANCED DRILLING HOSE

Used for delivery of high pressure drilling fluid mixed with gas while unbalanced drilling technology applied, such as drilling fluid mixed with nitrogen, air, mixed gas from air and nitrogen, or natural gas. Handles gas mixtures for foaming and lightening fluid weight.



 4326999337

PREMIUMHOSES.COM
PO BOX 81106, MIDLAND TX 79708

PREMIUM DRILLING HOSES

TYPE	INSIDE DIAMETER IN	OUTSIDE DIAMETER IN	WORKING PRESSURE PSI	TEST PRESSURE PSI	FLAME SHIELD YES/NO	WEIGHT LBS/FT	MBR OPERATING IN
------	-----------------------	------------------------	-------------------------	----------------------	------------------------	------------------	---------------------

HIGH PRESSURE BUILT-IN END MUD HOSES

NJG	2.00	3.58	5,000	10,000	NO	12.77	35.43
NNG	2.00	4.17	5,000	10,000	YES	15.25	35.43
NJG	2.50	4.06	5,000	10,000	NO	19.49	35.43
NNG	2.50	4.65	5,000	10,000	YES	22.17	35.43
NJG	3.00	4.72	5,000	10,000	NO	30.24	47.24
NNG	3.00	5.28	5,000	10,000	YES	32.60	47.24
NJG	3.50	5.28	5,000	10,000	NO	27.55	51.18
NNG	3.50	5.75	5,000	10,000	YES	29.57	51.18
NJG	4.00	6.30	5,000	10,000	NO	18.14	55.12
NNG	4.00	6.80	5,000	10,000	YES	20.16	55.12
NJG	5.00	7.52	5,000	10,000	NO	32.25	59.05
NNG	5.00	8.07	5,000	10,000	YES	34.27	59.05
NJG	6.00	8.82	5,000	10,000	NO	39.65	70.87
NNG	2.00	4.06	7,500	15,000	NO	41.66	47.24
NJG	2.50	4.88	7,500	15,000	NO	12.77	47.24
NNG	2.50	5.35	7,500	15,000	YES	15.25	47.24
NJG	3.00	5.43	7,500	15,000	NO	19.49	51.18
NNG	3.00	5.98	7,500	15,000	YES	22.17	51.18
NJG	3.50	5.98	7,500	15,000	NO	30.24	55.12
NNG	3.50	6.57	7,500	15,000	YES	32.59	55.12
NJG	4.00	6.61	7,500	15,000	NO	27.55	59.05
NNG	4.00	7.17	7,500	15,000	YES	29.57	59.05
NJG	5.00	8.03	7,500	15,000	NO	18.14	62.99
NNG	5.00	8.58	7,500	15,000	YES	20.16	62.99
NJG	6.00	9.76	7,500	15,000	NO	32.25	70.87

HIGH PRESSURE BUILT-IN END CEMENT HOSES

SNG	2.00	4.06	10,000	15,000	NO	12.77	47.24
NSG	2.00	4.69	10,000	15,000	YES	15.25	47.24
SNG	2.50	4.94	10,000	15,000	NO	19.49	51.18
NSG	2.50	5.57	10,000	15,000	YES	22.17	51.18
SNG	3.00	5.98	10,000	15,000	NO	30.24	55.12
NSG	3.00	6.50	10,000	15,000	YES	32.59	55.12
SNG	4.00	6.42	10,000	15,000	NO	27.55	59.05
NSG	4.00	6.93	10,000	15,000	YES	29.57	59.05
SNG	2.00	4.57	15,000	22,500	NO	18.14	51.18
NSG	2.00	5.08	15,000	22,500	YES	20.16	51.18
SNG	2.50	5.91	15,000	22,500	NO	32.25	59.05
NSG	2.50	6.42	15,000	22,500	YES	34.27	59.05
SNG	3.00	6.61	15,000	22,500	NO	39.65	62.99
NSG	3.00	7.13	15,000	22,500	YES	41.66	62.99

BUILT-IN END UNBALANCED DRILLING HOSES

UDG	2.00	4.17	5,000	10,000	NO	6.72	35.43
UDG	2.50	4.60	5,000	10,000	NO	10.75	39.37
UDG	2.50	5.35	7,500	15,000	NO	15.45	47.24
UDG	3.00	5.28	5,000	10,000	NO	12.09	47.24
UDG	3.00	5.98	7,500	15,000	NO	14.45	51.18
UDG	3.50	5.75	5,000	10,000	NO	14.78	55.12
UDG	3.50	6.57	7,500	15,000	NO	24.86	59.05
UDG	4.00	6.80	5,000	10,000	NO	23.52	59.05
UDG	4.00	7.08	7,500	15,000	NO	27.55	62.99
UDG	5.00	8.11	5,000	10,000	NO	36.29	62.99
UDG	5.00	8.66	7,500	15,000	NO	45.69	66.93



10810 STATE HWY 191, UNIT 3
MIDLAND, TX 79707