

NeverStrip Gloss™

Parts A+B





Neverstrip Gloss, Part A

Safety Data Sheet

1 of 3

Safety Data Sheet

Section [1] Product and Company Identification

Product Name: NeverStrip Gloss, Part A

Manufacturer: NeverStrip Floor Coatings, 2816 Centre Cir, Downers Grove, IL 60515

Information: 800.854.5414

E-mail: Info@NeverStrip.com

Date Prepared: 6/26/2025

Prepared by: NeverStrip Floor Coatings

Section [2] Hazards Identification

Components	CAS#	OSHA	PEL	WT%
None	N/A	NE	NE	NE

This product contains no hazardous ingredients as defined under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

NE - Not Established

HMIS Ratings

Health 1 **Flammability 0** **Reactivity 0** **Protection C**

0 = Insignificant Hazard, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

C = Safety Glasses, Synthetic Gloves, Synthetic Apron

Global Hazard System

Hazard Symbols: None

Key Word: Irritant

Section [3] Composition / Information on Ingredients

Boiling Range: 212°F

Vapor Density (Air=1.0): .569 air

Vapor Pressure: 29.33 mm Hg@68°F

Solubility in Water: Dispersible

Appearance and Odor: Slight ammonia odor

Specific Gravity (H2O=1): 1.05

Evaporation Rate (Butyl Acetate=1): .38 (Butyl acetate=1)

Section [4] Fire and Explosion Hazard

Flash Point: >250°F

Method Used: Setaflash

Flammable Limits in Air by Volume - Lower: 25.00 **Upper:** 16.00

Extinguishing Media: Carbon Dioxide, Dry Chemical, Foam and/or Water Fog.

Gloss

Neverstrip Gloss, Part A

Safety Data Sheet

OSHA Flammability Classification:

Special Fire Fighting Procedures: Fire fighters must wear self contained breathing apparatus or air masks. Containers exposed to fire should be kept cool with water spray. Do not spray fire directly. A solid stream of water directed into the hot burning liquid could cause frothing.

Unusual Fire and Explosion Hazards: None

Section [5] Reactivity Data

Stability: Stable

Conditions to Avoid: None

Incompatibility (Materials to Avoid): None

Hazardous Decomposition or By-Products: By Fire: CO₂, CO, and other aliphatic fragments.

Hazaedous Polymerization: None

Section [6] Hazards Identification / First Aid Measures

Health Risks and Symptoms of Exposure: None

INHALATION: Harmful if inhaled. May affect the brain, nervous system or respiratory system causing dizziness, headache, nausea or respiratory irritation.

Skin: May cause irritation.

Eyes: May cause irritation.

Skin Absorption: Can be absorbed through the skin.

Ingestion:

Health Hazards (Acute and Chronic): Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains ingredients which may cause liver damage, kidney damage, mucous membrane irritation.

Carcinogenicity NTP Carcinogen: IARC Monographs: OSHA Regulated:

Medical Conditions Generally Aggravated by Exposure: Proposition 54 Statement:

Warning! This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Medical conditions generally aggravated by exposure - any respiratory or skin condition.

Emergency and First Aid Procedures:

Eyes: Flush immediately with water for at least 15 minutes and get medical attention.

Skin: Wash thoroughly with soap and water.

Ingestion: If swallowed, get medical attention immediately.

Inhalation: If affected by inhalation of vapor or spray mist, remove to fresh air.

Possible Routes of Entry: Inhalation, ingestion and skin absorption.

Section [7] Handling and Storage

Steps to be Taken in Case Material is Released or Spilled: Ventilate area. Avoid breathing of vapors. Use self-contained breathing apparatus or air mask for large spills

in a confined area. Eliminate ignition sources. Remove with inert absorbent and non-sparking tools. Avoid contact with eyes.

Waste Disposal Method: Dispose in chemical disposal area or in a manner that complies with local, state, and federal regulations. Do not incinerate closed containers.

Precautions to be Taken in Handling and Storing: Containers should be grounded/bonded when pouring. Avoid free fall of liquid in excess of a few inches. Keep away from heat, sparks and open flames. Keep containers closed when not in use.

Do not store above 120°F. Based on the product flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106.

Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture, or weld on or near container. All label warnings must be observed until the container has been cleaned or reconditioned.

Section [8] Exposure Controls / Personal Protection

Respiratory Protection: Wear appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring vapor/mist levels are below applicable limits. Follow respirator manufacturer's directions for respirator use.

Ventilation: Required for handling in a confined area, ventilation equipment should be explosion proof. Eliminate ignition sources.

Protective Gloves: Usual hand protection for handling resin products.

Eye Protection: A minimum of safety glasses with side shields for handling Resin materials.

Other Protective Clothing or Equipment: Usual clothing for handling resin products.

Section [9] Regulatory Information

DOT Proper Shipping Name: Polyester Resin Dispersion

Proper Shipping Name: Synthetic Resin Liquid

Hazard Class: Not Regulated by DOT, IMO, or ICAO

UN/NA ID Number: NE

Packing Group: NE

Section [10] Other Information

Disclaimer: The information contained herein is based on the data available to us and is believed to be correct. NeverStrip Floor Coatings makes no warranty expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.

NeverStrip Floor Coatings assumes no responsibility for injury, loss or damage from the use of the product described.

NeverStrip Floor Coatings, 800.854.5414 www.NeverStrip.com

For Hazardous Materials Incident: Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC (24 hours) USA and Canada: 800.424.9300