

Category: Micron Film

System: Non-Resilient Clean & Seal

Product: NeverStrip Stone, Terrazzo and Concrete Seal™

Surface: Concrete, Terrazzo, non-resilient surfaces



- 1)** Thoroughly strip and clean the substrate so it is free of all wax and sealer residue. Allow the surface to dry completely before proceeding.
- 2)** Mix, gently shake or stir thoroughly before applying.
- 3)** Apply 1st coat of Stone, Terrazzo and Concrete Seal™ at approximately 4,000-6,000 SF per gallon. Allow to dry for 5-15 minutes.
- 4)** Apply 2nd coat of Stone, Terrazzo and Concrete Seal™ at approximately 4,000-6,000 SF per gallon on top of the 1st coat. Allow to dry for 5-15 minutes. Do not burnish.
- 5)** Maintain floor luster using NeverStrip Micron Clean™ with daily cleaning. 1 oz. per gallon of water.
- 6)** Every 30 Cleanings (once a month) use NeverStrip Micron Restore™ in auto scrubber (4 – 12 oz. per gallon of water) for optimal results with White or Red cleaning pads.

PLEASE NOTE: It can also assist to scrub floor with Micron Restore™ in an auto scrubber the first week, to reduce marks/scuffs on floor.

IMPORTANT:

- Additional instructions on Product Data Sheets and other resources are available at www.neverstrip.com.



Micron Floor Coatings for the New Millennium
neverstrip.com

