

Cleaning & Maintenance

Micron Sealers have four effective sheen levels, as follows:

Gloss (achieved by burnishing original Micron Sealer formula)

Satin (original formula, not burnished)

Lower Satin Sheen product

Matte (available with Micron Shield product for all hard surfaces)



Micron Sealers

- **Liquid Grip** for higher traction on wet floors
- **Micron Shield** for use on any hard surface: **1)** without any enhancement of the surface; **2)** no change of the sheen including maintaining a Matte sheen and **3)** providing the highest level of stain resistance
- **Rubber Seal** for Rubber flooring
- **Stone, Terrazzo and Concrete Seal** for Natural Stone, Terrazzo and Concrete
- **Tile Seal** for Ceramic, Porcelain, Quarry Tile, Brick and Pavers
- **Vinyl Seal** for resilient flooring including: VCT, LVT, Linoleum, and Sheet Vinyl
- **Wood & Cork Seal** for Natural Wood and Cork floors



Satin Sheen Micron Sealer

Daily/Ongoing Floor Care

Maintain proper, effective matting at entrances to capture particulates from entering the facility.

Dust mop, sweep, or vacuum as needed to remove dry, abrasive soils. Scrub and extract as needed with **Red or Blue scrubbing pads** with **NeverStrip Micron Clean** (1-2 oz./gal. of water) or with a **NeverStrip Micron Clean and Buff Pad** (8000 grit) to clean and enhance the shine of the Micron Sealer.

Burnish with **NeverStrip Diamond Burnishing Pad** (8000 grit) for added shine.

As needed, remove stains; surface scratches or other imperfections by scrubbing the Micron Sealer with a 175 rpm floor machine or equivalent using a **NeverStrip Micron Restoration Pad** (3500 grit) with **NeverStrip Micron Restore Cleaner** at 10 oz./gallon of water.

Once Every 30 Cleanings

Scrub and extract the **NeverStrip Micron Restore Cleaner** (10 oz/gal of water) using an auto scrubber; 175 rpm floor machine or equivalent with a **NeverStrip Micron Restoration Pad**. The **Micron Restore** applies "elements" of the Micron Sealer technology onto the Micron Sealer. **The Micron Restoration Pad** removes soil, blemishes, scuffs, marks, and surface scratches from the Micron Sealer,

Please note, cleaning and maintaining the floor **only** with a conventional mop or microfiber pad is not recommended. A conventional mop or microfiber pad alone **will not** efficiently remove soil and particulate; remove marks and scuffs or buff out surface scratches from the sealer.

Satin Micron Sealer Reapplications

As needed, clean the **Satin Micron Sealer** and apply one or two new applications of the desired **Satin Micron Sealer**. The application rate is typically 6,000 sq. feet per gallon per coat. No need to strip the Micron Sealer during its normal lifecycle.



Lower Satin Sheen Micron Sealer

Daily/Ongoing Floor Care

Maintain proper, effective matting at entrances to capture particulates from entering the facility.

Dust mop, sweep, or vacuum as needed to remove dry, abrasive soils.

Scrub and extract as needed with **Red or Blue scrubbing pads** with **NeverStrip Micron Clean (1-2 oz./gal. of water)**.

Do not use Micron Diamond Pads or burnish the Lower Satin Sheen Micron Sealers

Once Every 30 Cleanings

Scrub the Lower Sheen Micron Sealer with a **Blue Scrubbing Pad** (10 oz/gal of water) using an auto scrubber or a 175 rpm floor machine or equivalent. The **Micron Restore** applies "elements" of the Micron Sealer technology onto the Micron Sealer.

Please note, cleaning and maintaining the floor only with a conventional mop or microfiber pad is **not** recommended. A conventional mop or microfiber pad alone **will not** efficiently remove soil and particulate; remove marks and scuffs or buff out surface scratches from the sealer.

Lower Satin Micron Sealer Reapplications

of As needed, clean the **Lower Satin Micron Sealer** and apply one or two new applications of the desired **Lower Satin Micron Sealer**. The application rate is typically 6,000 sq. feet per gallon per coat. No need to strip the Lower Satin Sheen Micron Sealer during its normal lifecycle.



Micron Shield

Daily/Ongoing Floor Care

Maintain proper, effective matting at entrances to capture particulates from entering the facility.

Dust mop, sweep, or vacuum as needed to remove dry, abrasive soils.

Scrub with **Red or Blue scrubbing pads** with **NeverStrip Micron Clean** (1-2 oz./gal. of water) and extract.

Do not use Micron Diamond Pads or burnish the Lower Satin Sheen Micron Sealers

Please note, cleaning and maintaining the **Micron Shield only** with a conventional mop or microfiber pad will not maintain the Micron Shield at a "high level" within a busy commercial facility. A conventional mop or microfiber pad **will not** or not efficiently remove marks and scuffs and will not buff out/remove surface scratches on the Sealer.

Micron Shield Reapplications

As needed, scrub the floor with water and a NeverStrip supplied **Enhanced Prep Pad**. Apply two or three applications of Micron Shield at 7,000 to 8,000 sq. feet per gallon per coat.

Liquid Grip

Daily/Ongoing Floor Care

Maintain proper, effective matting at entrances to capture particulates from entering the facility.

Sweep, or vacuum as needed to remove dry, abrasive soils.

Scrub and extract as needed with a **Red or Blue equivalent brush** with **NeverStrip Micron Clean** (1-2 oz./gal. of water).

Do not use a string mop or microfiber flat mop to clean Liquid Grip.

Once Every 30 Cleanings

Scrub and extract the NeverStrip Micron Restore Cleaner (10 oz/gal of water) using an auto scrubber; 175 rpm floor machine or equivalent with a Blue Brush. The Micron Restore applies "elements" of the Micron Sealer technology onto the Micron Sealer.



Do:

- ✓ Follow NeverStrip's recommended floor care procedures
- ✓ Clean spills quickly
- ✓ Keep water off the floor for 8 hours after Sealer application
- ✓ Use NeverStrip Microbot Grease Eliminator to clean oils and greases from the Sealers
- ✓ Use NeverStrip Micron Clean for daily/frequent cleaning (1 oz./gallon of water)
- ✓ Use NeverStrip Micron Restore every 30 cleanings
- ✓ Use NeverStrip pads to maintain the Sealers
- ✓ Use soft brushes to clean NeverStrip Liquid Grip
- ✓ Use NeverStrip Floor Protectors on moveable furniture to prevent scratching
- ✓ Use proper matting to reduce soil load from the outside
- ✓ Use catch trays or place alcohol hand sanitizer dispensers over counters;
- ✓ Spot repair as desired

Do Not:

- ✗ Use only traditional string mops or microfiber pads to clean Micron Sealers
- ✗ Use cleaners with d-limonene or any citrus cleaners
- ✗ Use rubber mats, which get saturated with water or urine
- ✗ Use Magic Eraser or equivalent material
- ✗ Use acid-based toilet and urinal cleaners
- ✗ Use pads to clean NeverStrip Liquid Grip
- ✗ Apply tape onto Micron Sealers without first verifying compatibility
- ✗ Allow water to puddle on Sealers - not applicable to Micron Shield

www.NeverStrip.com • 847-881-4404 • orders@neverstrip.com