

NeverStrip Microbot Grease Eliminator

Microbot Grease Eliminator

Product Description

Microbot Grease Eliminator is based on 21st Century floor care technology. This product removes asphalt walkoff brought in from parking lots, and oils and greases from hard-surface flooring with less labor, less time and less odors than caustic, high pH products.

Microbot Grease Eliminator Transforms oils and greases into water and carbon dioxide by incorporating specific, naturally occurring Basilica microbes (bacteria) as a greener alternative to harsh chemicals/degreasers, to digest/eliminate organic materials without the need for special equipment or expertise. Address hydrocarbon greases and oils on a daily basis more safely and effectively.

Key Features

- Removes asphalt walkoff, hydrocarbon oils, and greases from commercial floors and other surfaces
- Cost effective
- Easy, fast process
- Address greases and oils on a daily basis without caustic, high pH degreasers
- Floors are less slippery while using product compared to high pH degreaser cleaners
- Low-odor formulation
- Continually address grease odors
- Near neutral pH
- Use on any non-carpet flooring
- When used as directed and where permitted by local regulations, the product may be disposed of through normal sanitary sewer system
- Aids in ongoing drain cleaning

Cleaning Instructions

Automotive repair shops, warehouses and other commercial facilities can continually address grease, oil and soil build-up.

An initial professional restorative cleaning using the Microbot Grease Eliminator is often a desired approach prior to less intensive daily or frequent cleaning. After the restorative cleaning, the facility can address greases and oils much more effectively and safely, on a daily basis, using a Mop and Bucket or auto scrubber.

Restorative Cleaning Process:

- Read entire product label before proceeding
- Sweep the floor
- Turn the Microbot quart-container over twice to mix solution (**DO NOT SHAKE**)
- Fill a mop bucket with **WARM** tap water
- Apply liberal amounts of water only to the floor
- In **WARM** Water dilute Microbot Grease Eliminator 11:1 (11 parts warm water to 1 part MGE)
- Apply mixed solution liberally onto the floor with a mop or sprayer
- Immediately scrub or agitate the solution on the floor with a 175-rpm floor machine or equivalent equipment with a soft to medium grit brush or pad appropriate for the floor type
- A deck brush is a good tool for small or tight areas and along baseboards
- Allow 15 minute dwell time
- Perform a second scrub
- Evaluate condition of floor to verify if additional scrub(s) are required
- If available, squeegee the solution to a drain (the Microbot solution will help clean the drain pipe of grease and oils)
- Using an extraction system (wet vac with squeegee wand, rinse and reclaim system - truck mounted or portable; or auto scrubber) extract the remaining solution. Be prepared to add a proper amount of defoamer product to the recovery tank to control foaming

Microbot Grease Eliminator

Restorative Cleaning Process (continued):

- Rinse the floor with clean water
- Pour used solution down drains, toilets and urinals to assist in cleaning; this reduces grease and oils and combats odors in your drains

Daily/Frequent Maintenance Cleaning Instructions

- Read entire product label before proceeding
- Sweep the floor
- Turn the Microbot quart-container over twice to mix solution (**DO NOT SHAKE**)
- In **WARM** Water dilute Microbot Grease Eliminator 11:1 (11 parts water to 1 part MGE)
- Mop the floor, wringing the mop as you go
- Allow floor to air dry (No need to rinse floor)
- Pour used solution down drains, toilets and urinals to assist in cleaning; this reduces grease and oils and reduces/eliminates odors in your drains

Auto Scrubber Cleaning Instructions

- Read entire product label before proceeding
- Sweep the floor
- Turn the Microbot container over twice to mix solution (**DO NOT SHAKE**)
- In **WARM** Water dilute Microbot Grease Eliminator 11:1 (11 parts water to 1 part MGE) in the auto scrubber for daily use

- Use a red pad or equivalent brush
- Scrub and Extract in normal fashion (Be prepared to add a proper amount of defoamer product to the recovery tank to control foaming) Pour used solution down drains, toilets and urinals to assist in cleaning; this reduces grease and oils and combats odors in your drains
- Pour used solution down drains, toilets and urinals to assist in cleaning; this reduces grease and oils and combats odors in your drains

Storage

- Two year shelf life from manufacturing date when properly stored and kept sealed
- Close container tightly after each use
- Store in original container only
- Store and use within temperatures of 40 degrees to 100 degrees fahrenheit
- **Do not** allow to freeze - Not Freeze/Thaw stable
- **Do not** allow temperature to exceed 100 degrees F for extended periods of time

Caution

- **Do not** allow product to freeze
- **Do not** mix product into hot water
- **Do not** ingest
- If ingested, seek immediate medical attention
- Wear protective eyewear
- Wear protective gloves
- **Do not** use product where it can come in contact with mastic, glue, soy based products, floor finish/wax or similar materials
- **Do not** use on surfaces with food contact or food prep



NeverStrip Floor Coatings
2816 Centre Circle
Downers Grove, IL 60515
630-330-1010
Info@neverstrip.com

