

NeverStrip®
FLOOR COATINGS
21st Century Floor Care Technology™

NeverStrip Resin Seal



NeverStrip Resin Seal

Resin Seal is a clear, inorganic based, high performance, micron thin, film treatment for all resin & epoxy flooring.

Resin Seal provides a natural, non-yellowing, clear appearance, which does not need to be stripped or removed in its normal lifecycle.

The sealer protects the flooring surface from stains, abrasion, scratches and overall abuse. The sealer offers an attractive wet coefficient of friction.

Resin Seal comes in two gloss levels: Low Satin Sheen and Satin Sheen. The Satin Sheen can be burnished for higher shine.

Characteristics

- Micron thin film (typical coverage of 5,000 to 6,000 sq. feet per gallon per application on non porous surface)
- Single component - no mixing, no pot life, ready to use
- For industrial, commercial or residential use
- For indoor or outdoor applications
- 10 minutes to reapply or walk on
- Low to slight odor
- No Hazardous ingredients: No zinc; No PFAS Chemicals
- Volume solids-23%
- Shelf life: 24 months from purchase date when kept securely closed
- 11.5 pH
- Meets State of California VOC Standards
- Meets ANSI and ASTM slip resistant standards for wet surfaces with both the BOT 3000E and Pendulum test methods
- Satin Sheen responds to burnishing for higher gloss
- Removable with chemical stripper or abrasion
- Enriches colors
- Excellent abrasion, scratch and stain resistance
- Lowers the ongoing cost of floor care with less required labor compared to many conventional floor care methods

- Excellent ongoing, simplistic refreshability is possible with NeverStrip cleaners and pads
- Multi-year performance between reapplications is common

Surface Preparation

Clean the floor; remove dust and particulate matter.

Abrasion of the flooring surface is **not** needed to achieve a desired adhesion.

Application

Turn over the container multiple times.

If the surface is porous, apply 2-3 applications of NeverStrip Micron Primer at 1,500 to 2,500 sq. feet per gallon per coat prior to applications of Resin Seal. A surface is considered porous if water readily penetrates and soaks into the substrate.

Spray Resin Seal onto small sections of the floor at a time and spread with a smooth, flat microfiber pad. Overlap continuously to avoid skips.

Click <https://www.youtube.com/shorts/HXXB5RI93kU> or scan the QR Code to view a popular application technique using an application tool widely available.



Two to three applications of Resin Seal is typical at 1,250 to 1,500 sq. feet per quart per application.

More Micron thin applications are best versus fewer heavy applications.

Keep water off the floor after application for a minimum of 8 hours.

NeverStrip Resin Seal

Caution

Do not overapply the sealer ("Thin to win").

Do not overwork the sealer.

Do not use cleaners containing Butyl, Citrus or Di-limonene.

Read and follow Product Data and Safety Data Sheets carefully.

Keep water off of the floor for 8 hours after application.

Micron Sealers do not want to be submerged in water for long periods of time, which can result in delamination.

Removal

Resin Seal does not need to be removed/ stripped in its normal lifecycle.

Removal can be accomplished using a high quality floor finish stripper with longer than typical dry times (50 minutes vs. 10 minutes) or by abrading the product off of the floor.

Cleaning & Maintenance

Click www.neverstrip.com/cleaning-maintenance or scan the QR code.



Packaging

- Sample, 8 oz. plastic bottle
- Quart, 32 oz. plastic bottle
- Gallon, 128 oz. plastic bottle

Coverage

1,250 to 1,500 sq foot coverage per quart per application is typical on a non-porous surface.



NeverStrip Floor Coatings
2816 Centre Circle
Downers Grove, IL 60515
847-881-4404
Info@neverstrip.com