

• MICRON RESILIENT - NON-BURNISHED • (LVT, LINOLEUM, ETC.)

Category: Micron

System: Micron Resilient (Non-Burnished)

Products: Vinyl Seal, Enviro-Pro, Micron Restore

Surface: Resilient Flooring (LVT, Linoleum, etc.)



- 1) Thoroughly strip and clean the substrate of any floor finish, soil, grease, etc.
- 2) Condition the floor dry with a weighted (ideally 160#) Square Scrub or equivalent machine with a NeverStrip Enhanced Prep Pad or 3M Surface Prep Pad. Then, auto scrub or equivalent, with water to remove dust.
- 3) Apply 1st coat of Vinyl Seal at approximately 4,000-6,000 SF per gallon with pump sprayer and 18" looped microfiber pad. Allow to dry. Typically 5-10 minutes.
- 4) Apply 2nd coat of Vinyl Seal at approximately 4,000-6,000 SF per gallon. Allow to dry for at least 15 minutes before opening floor to traffic.
- 5) Maintain floor using NeverStrip Micron Clean for frequent cleaning. 1 oz. per gallon of water.
- 6) Monthly or as needed, use NeverStrip Micron Restore in auto scrubber (4 – 12 oz. per gallon of water) with red cleaning pad.
- 7) When ready to apply a new coat or two of Vinyl Seal, scrub the floor with a green pad using NeverStrip Micron Restore, 12 oz. to a gallon of water. Extract and allow the floor to dry. Apply 1 or 2 applications of Vinyl Seal.

PLEASE NOTE: It can also assist to scrub floor with Micron Restore in an auto scrubber the first week, to reduce marks/scuffs on floor.

IMPORTANT:

Additional instructions on Product Data Sheets and other resources are available at www.neverstrip.com.



neverstrip.com