

**NeverStrip®**  
FLOOR COATINGS  
21st Century Floor Care Technology™

# NeverStrip HD Masonry Cleaner



# NeverStrip HD Masonry Cleaner

**NeverStrip HD Masonry Cleaner** is a high-performance, heavy-duty restoration cleaner designed for the most difficult masonry cleaning applications. It is formulated to remove deep-set contamination including embedded dirt, grease, oil, and environmental buildup from porous mineral surfaces.

Engineered for use on heavily soiled substrates, this cleaner restores the natural appearance of limestone, sandstone, concrete, and exposed aggregate surfaces. It is particularly effective for exterior restoration projects where aggressive cleaning is required without damaging the substrate.

NeverStrip HD Masonry Cleaner is ready to use and designed to simplify the cleaning process by allowing the product to dwell and do the work.

## Key Features

- Heavy-duty cleaner designed for extreme contamination
- Effectively removes grease, oil, and embedded soils
- Restores the natural appearance of masonry surfaces
- Ready-to-use formulation
- No pre-wetting required prior to application
- Extended dwell capability with no rush rinsing required
- Can dry on the surface without reducing effectiveness
- Suitable for large-scale exterior cleaning projects
- Always verify compatibility using a patch test prior to full application

## Cleaning Instructions

### Patch Test (Required Prior to Use)

- Apply a small amount of product to an inconspicuous area using a brush
- Product begins working immediately upon application

- Allow sufficient dwell time before rinsing
- Typical dwell time may range from a few minutes up to 30–60 minutes depending on contamination level
- Rinse thoroughly with water and allow the test area to dry
- If results are satisfactory, proceed with full application
- If not, adjust dwell time accordingly and retest

### Cleaning Process

- Apply to a dry surface; pre-wetting is not required
- Use a brush, roller, or sprayer to thoroughly saturate the surface
- Allow the product time to work based on patch test results
- Product may remain on the surface for extended periods without risk of damage from drying
- After sufficient dwell time, rinse thoroughly with water
- For heavily soiled exterior surfaces, pressure washing is recommended for effective removal

### Spray Application Instructions

- Apply using a pump sprayer or low-pressure electric sprayer (50–60 psi)
- Use a fan spray nozzle to achieve full surface saturation
- Apply in a soaking manner, not as a mist
- Avoid wind drift during application
- Do not apply through a pressure washer, as this will dilute the product
- Do not use airless sprayers that atomize the solution

### Rinse

- Rinse thoroughly with water after dwell time is complete
- High-pressure water is recommended for heavily soiled surfaces
- Ensure all loosened contaminants are fully removed from the surface

## Limitations

- Not designed to remove graffiti or paint
- May not remove hardened mineral crusts or certain deep-set stains
- If no cleaning occurs, a coating or sealer may be present and must be removed prior to use
- Always verify surface compatibility with a patch test prior to full application

## Coverage

- Approximate coverage: 150 to 250 sq. ft. per gallon
- Coverage will vary depending on surface porosity and level of contamination

# NeverStrip HD Masonry Cleaner

## Temperature Range

- Product effectiveness decreases in colder temperatures
- Do not use below 50°F (10°C)

## Storage

- Keep containers sealed when not in use
- Store at temperatures above 50°F (10°C) to prevent crystallization
- Product may darken over time without affecting performance
- Shelf life is maintained when properly stored and not allowed to crystallize

## Precautions

- Protect all adjacent surfaces during use
- May cause permanent damage to glass, soft metals, and glazed finishes
- Protect windows, fixtures, and surrounding materials prior to application
- Protect vegetation, as contact may cause browning or damage
- Prevent runoff from contacting plant roots or sensitive areas
- Avoid wind drift during application
- Always test surfaces prior to full application

## Safety

- Wear rubber gloves and safety goggles during use
- Use proper ventilation in enclosed areas
- If product comes into contact with skin or eyes, rinse immediately with water
- Refer to Safety Data Sheet (SDS) for additional safety information

## Environmental Information

- Readily biodegradable
- Contains no VOCs
- When used properly, poses no significant environmental risk
- Dispose of waste in accordance with local, provincial/state, and federal regulations



2816 Centre Circle  
Downers Grove, IL 60515  
630-330-1010  
Info@neverstrip.com

5/11/26

© NeverStrip Floor Coatings