System: Micron Clean & Seal

**Products:** NeverStrip Tile Seal and Deep Clean or Microbot Grease Eliminator **Surfaces:** Ceramic, Porcelain, Quarry Tile



# 1. Preparation

- Thoroughly strip and clean the substrate to remove all wax, sealers, soil, and greases.
- For floors not requiring stripping, use **NeverStrip Deep Clean** for exceptional results.
- For greasy kitchen/restaurant floors:
- Use <u>NeverStrip MicroBot Grease Eliminator</u> for initial deep clean and ongoing maintenance.
- It effectively eliminates greases, oils, and soils when used daily.

## 2. Confirm Compatibility (adhesion)

- Apply <u>Tile Seal</u> on a small area: If the sealer separates like oil and water or shows fish-eyes, the surface tension is unsuitable for sealer application.
- Unlike resilient flooring, these harder surfaces do not respond to modification of surface tension with a pad.

## 3. Main Application

- Apply 2-3 coats of Tile Seal on ceramic, porcelain, and quarry tile: Two coats are sufficient if the sealer's appearance is attractive.
- Spread rate: 5,000 6,000 sq. feet per gallon per application on non-porous surfaces (first application may cover less).

## Application methods:

Use a quality <u>Microfibre Spray Mop Applicator</u> (using <u>this method</u>) or a standard garden pump sprayer with a dripless brass tip.

Pre-dampen the microfibre pad with the sealer before application.

- If using a pump sprayer, spray just ahead of spreading.
- Avoid too much product; if the product appears white, it is over-applied.
- Avoid "playing" with the sealer too much.
- Spread product onto adjoining sections by a couple of inches to avoid skips.
- Allow 10-15 minutes for drying before applying the next coat or resuming typical commercial traffic.
- Allow 25 minutes of dry time before burnishing.

## 4. Post-Application Care

- Keep water off the floor for 8 hours.
- Best practice: During the first week or two, scrub the floor with a red pad and Micron Clean (2 oz./gallon of water), then burnish to remove marks, scuffs, and surface scratches.

## **Additional Resources**

• Visit www.neverstrip.com for Product Data Sheets and other resources.

VeverStrip

Tile Sea

Cleaning and maintenance instructions available <u>here</u>.

