

NeverStrip[®]
FLOOR COATINGS
21st Century Floor Care Technology™

NeverStrip Liquid Grip™

Step 1 and Step 2



Liquid Grip is a high-traction, Micron-thin sealer system for WET floors. This rapid in-use, low to no-odor system provides a durable, high-performance, non-yellowing surface for residential and commercial environments.

Liquid Grip can be applied onto virtually any hard flooring surface including: ceramic, porcelain, quarry tile, concrete, terrazzo, VCT, LVT, linoleum, rubber, cork, sheet vinyl and other coatings such as urethane, epoxy and floor finish.

Applications include restaurants, retail, restrooms, showers, locker rooms, ramps, stairs, operating and emergency rooms and pool decks or anywhere higher traction is desired.

Characteristics

- Allow light foot traffic one (1) hour after completed application of **Step 2 Product**. Keep water off the surface for at least 8 hours but preferably 24 hours after completion of **Step 2 Product**.
- Wet static coefficient of friction of 0.80 has been recorded with the BOT 3000 E Universal Walkway Tester.
- Wet dynamic coefficient of friction of 0.57 has been recorded with the BOT 3000 E Universal Walkway Tester.
- The Liquid Grip System is not meant to be submerged under water or continuously wet. The system works well with periodic running water over the surface. The surface does need to dry between wet events.
- Clean with a soft brush. Do not use a pad. Avoid aggressive cleaning so as not to loosen the Liquid Grip's fine aggregate. Do not use citrus cleaners or cleaners with D-Limonene. Do use NeverStrip Micron Clean at 1-2 oz./gallon of water.
- Do use Microbot Grease Eliminator to remove greases, oils, urine, soap scum etc. before application of Liquid Grip and for ongoing cleaning.
- Liquid Grip is best applied by an experienced, professional floor care maintenance contractor.
- Liquid Grip has a Satin to Low Satin sheen.
- Liquid Grip is freeze/thaw stable.
- Liquid Grip is not typically stripped or removed in its normal lifecycle.
- Clean and seal with a new application of **Step 1 Product** and **Step 2 Product** as needed. No need to condition or abrade the surface prior to application.
- Shelf Life is one year from NeverStrip sale.
- Do not dilute the product.

Coverage

400-500 sq. feet per kit

Packaging

The Liquid Grip System consists of two 1 quart bottles (0.946 liters) and three 9", 3/8" nap microfiber roller covers.

The first step is to apply the appropriate Micron Sealer to the floor (Tile Seal for Ceramic/Porcelain; Vinyl Seal for Resilient Flooring, etc.).

Application

- 1 Flooring surface should be dry, clean and free of soil, grease, oils and other contaminants.
- 2 The first step is to apply one application of Micron Sealer to the floor (Tile Seal for Ceramic/Porcelain; Vinyl Seal for Resilient Flooring, etc.).

Shake **Step 1 Product** well. Pour entire contents of **Step 1 Product** quart container into a 7-gallon application tub with high 8" sides. This tub can be purchased at Home Depot in the cement mixing product area. Using a NeverStrip supplied, microfiber roller cover, agitate the Liquid Grip **Step 1 Product** with each dip of the roller cover into the black application tub. Do not pour more than one quart of **Step 1 Product** into the tub at a time. The NeverStrip Grip Aggregate is heavy. It quickly sinks to the bottom of the tub. Agitation with each dip is critical for achieving an even distribution of the aggregate across the floor. After each dip of the roller cover, apply the product onto approximately a 4' x 8' area. This application method should produce a coverage of approximately 350-400 sq. feet per kit. Pour any unused **Step 1 Product** back into its original container using a funnel and close the container securely.

- 3 The Liquid Grip **Step 1 Product** will often separate (like oil and water) during its application. This appearance is eliminated by an optional dry rolling of the still wet but drying Liquid Grip **Step 1 Product** with a new, dry, 3/8" nap microfiber roller cover about 5-10 minutes after applying the **Step 1 Product**. The roller cover used with this dry rolling process is provided as part of the Liquid Grip Kit.

It is helpful for whomever is performing the dry rolling process to wear golf shoes with plastic golf spikes or equivalent, so this person can, as needed, walk into/onto the wet Liquid Grip

The dry rolling process can be done by the same person who applies the Liquid Grip Step 1 Product or can be performed by a second individual. Allow **Step 1 Product** to dry at least 30 minutes before applying **Step 2 Product**.

- 4 **Step 2 Product** can be poured into the black applicator tub as needed. No need to pour the entire quart content at once since the **Step 2 Product** does not have any Grip Aggregate. After **Step 1 Product** has dried to the touch (or at least 20-30 minutes), apply **Step 2 Product** using the same Dip and Roll method as **Step 1 Product** with the same expected 400-500 sq. feet of coverage per quart. Use the second supplied 9" microfiber roller cover to apply **Step 2 Product**.
- 5 Wait one hour before allowing any foot or cart traffic on the floor.
- 6 Keep water off the floor for at least 8 hours.

Cleaning and Maintenance

Go to www.neverstrip.com/cleaning-maintenance.



847-881-4404
orders@neverstrip.com
www.neverstrip.com