

• SINGLE COAT •

Category: Thin Film

System: Single Coat

Product: NeverStrip Gloss, Satin, Matte or High Solids Urethane

Surface: VCT, LVT, Sheet Vinyl, Rubber, Wood, VAT, Cork, Bamboo, Recycled Vinyl



- 1)** Remove any floor finish or sealers (NeverStrip supplied stripping pads and stripper recommended for removal of floor finish)
- 2)** Clean the floor with appropriate cleaner depending on conditions. Profi Cleaner by Taski is an outstanding product.
- 3)** Clean the floor with an auto scrubber or rinse and reclaim system. Let the floor thoroughly dry.
- 4)** Vacuum and dry tack the floor to pick up lint, hair, etc. NeverStrip supplied Tack Cloth is an effective dry tacking method.
- 5)** Apply tape to all surfaces that one does not want coated.
- 6)** Apply NeverStrip Urethane coating of choice (Gloss, Satin or Matte) at 350-425 sq. feet per gallon (4-6 wet mils) using a 3/8" nap woven roller cover.

Apply the NeverStrip High Solids Urethane at 450 – 500 sq. feet per gallon (2-3 wet mils) using a 1/4" nap woven roller only.

7) Optional: Two coats may be desired due largely to the porosity of the floor. Two coats are typically used on more porous surfaces such as wood, cork and bamboo. In the case of wood flooring, please note that you will want to let the floor dry at least 8 hours (preferable 10-12) and then use an EPP pad to lightly abrade the coating prior to applying the 2nd coat. This knocks down any fibers that might have stood up during the first application.

Apply the 2nd coat, at 4-6 wet mils, using a 3/8" nap woven roller cover. Let dry for 8 hours before allowing traffic on floor.

IMPORTANT:

- Additional instructions on Product Data Sheets and other resources are available at www.neverstrip.com.



Micron Floor Coatings for the New Millennium
neverstrip.com