

**NeverStrip®**  
FLOOR COATINGS  
21st Century Floor Care Technology™

# NeverStrip Micron All-Surface Sealer (MASS)



# NeverStrip Micron All-Surface Sealer

**Micron All-Surface Sealer (MASS)** is a clear, inorganic based, high performance, micron thin, film treatment for any and all non-carpet flooring surfaces.

Micron All-Surface Sealer provides a natural, non-yellowing, clear appearance, which does not need to be stripped or removed in its normal lifecycle.

The sealer protects the flooring surface from stains, abrasion, scratches and overall abuse. The sealer offers an attractive wet coefficient of friction.

Micron All-Surface Sealer comes in two gloss levels: Low Satin Sheen and Satin Sheen. The Satin Sheen can be burnished with **NeverStrips's Micron Burnishing Pad** for a higher shine.

## Characteristics

- Micron thin film (typical coverage of 5,000 to 6,000 sq. feet per gallon per application on non porous surface)
- Single component - no mixing, no pot life, ready to use
- For industrial, commercial or residential use
- For indoor or outdoor applications
- 10 minutes to reapply or walk on
- Low to slight odor
- No Hazardous ingredients: No zinc; No PFAS Chemicals
- Volume solids-23%
- Shelf life: 24 months from purchase date when kept securely closed and in a temperature controlled environment
- 11.5 pH
- Meets State of California VOC Standards
- Meets ANSI and ASTM slip resistant standards for wet surfaces with both the BOT 3000E and Pendulum test methods
- Satin Sheen responds to burnishing for higher gloss
- Removable with chemical stripper or abrasion
- Enriches colors
- Excellent abrasion, scratch and stain resistance
- Lowers the ongoing cost of floor care with less required labor compared to many conventional floor care methods

- Excellent ongoing, simplistic refreshability is possible with NeverStrip cleaners and pads
- Multi-year performance between reapplications is common

## Surface Preparation

Completely remove any floor finish/acrylic/wax.

Clean the floor; remove dust and particulate matter.

Abrasion of the flooring surface is **not** needed to achieve a desired adhesion.

## Application

Turn over the container multiple times.

If the surface is porous, apply 2-3 applications of NeverStrip Micron Primer (VCT) or Densi-Prime (Concrete/Stone) at 1,500 to 2,500 sq. feet per gallon per coat prior to applications of Micron All-Surface Sealer. A surface is considered porous if water readily penetrates and soaks into the substrate.

First, spray a small amount of Micron All-Surface Sealer directly onto a new microfiber applicator flat pad, then spray Micron All-Surface Sealer onto a small section of the floor and spread (work in 18" x 3' sections). Overlap continuously to avoid skips.

Do not overapply ("Thin to win"). Do not overwork the sealer. Just spray, spread, and move to next section.

Let the sealer dry for 10 minutes before reapplying or walking on it.

Click <https://www.youtube.com/shorts/HXXB5RI93kU> or scan the QR Code to view a popular application technique using an application tool widely available.



Two to three applications of Micron All-Surface Sealer is typical at 5,000-6,000 SF/gallon/application or 1,250 to 1,500 SF/quat/application.

More Micron thin applications are best versus fewer heavy applications.

Keep water off the floor after application for a minimum of 8 hours.

# NeverStrip Micron All-Surface Sealer

## Caution

Do not overapply the sealer ("Thin to win").

Do not overwork the sealer (This will cause streaking).

Do not use cleaners containing **Butyl, Citrus** or **Di-limonene**.

NeverStrip strongly recommends the use of our cleaner, **Micron Clean**, on a daily basis and our restorative cleaner, **Micron Restore**, on a periodic basis. Also, please ask about our **Micron Daily Clean & Buff Pad**.

Read and follow Product Data and Safety Data Sheets carefully.

Keep water off of the floor for 8 hours after application.

Micron Sealers do not want to be submerged in water for long periods of time, which can result in delamination.

## Removal

Micron All-Surface Sealer does not need to be removed/stripped in its normal lifecycle.

Removal can be accomplished using a high quality floor finish stripper with longer than typical dry times (50 minutes vs. 10 minutes) or by abrading the product off of the floor.

## Cleaning & Maintenance

Click [www.neverstrip.com/cleaning-maintenance](http://www.neverstrip.com/cleaning-maintenance) or scan the QR code.



## Packaging

- Sample, 8 oz. plastic bottle
- Quart, 32 oz. plastic bottle
- Gallon, 128 oz. plastic bottle

## Coverage

5,000-6,000 SF/gallon/application or 1,250 to 1,500 SF/quart/application



NeverStrip Floor Coatings  
2816 Centre Circle  
Downers Grove, IL 60515  
Info@neverstrip.com