

NeverStrip®
FLOOR COATINGS
21st Century Floor Care Technology™

NeverStrip Micron All-Surface Sealer (MASS)



NeverStrip Micron All-Surface Sealer

Micron All-Surface Sealer (MASS) is a clear, inorganic based, high performance, micron thin, film treatment for any and all non-carpet flooring surfaces.

Micron All-Surface Sealer provides a natural, non-yellowing, clear appearance, which does not need to be stripped or removed in its normal lifecycle.

The sealer protects the flooring surface from stains, abrasion, scratches and overall abuse. The sealer offers an attractive wet coefficient of friction.

Micron All-Surface Sealer comes in two gloss levels: Low Satin Sheen and Satin Sheen. The Satin Sheen can be burnished with **NeverStrip's Micron Burnishing Pad** for a higher shine.

Characteristics

- Micron thin film (typical coverage of 5,000 to 6,000 sq. feet per gallon per application on non-porous surface)
- Single component - no mixing, no pot life, ready to use
- For industrial, commercial or residential use
- For indoor or outdoor applications
- 10 minutes to reapply or walk on
- Low to slight odor
- No Hazardous ingredients: No zinc; No PFAS Chemicals
- Volume solids-23%
- Shelf life: 24 months from purchase date when kept securely closed and in a temperature controlled environment
- 11.5 pH
- Meets State of California VOC Standards
- Meets ANSI and ASTM slip resistant standards for wet surfaces with both the BOT 3000E and Pendulum test methods
- Satin Sheen responds to burnishing for higher gloss
- Removable with chemical stripper or abrasion
- Enriches colors

- Excellent abrasion, scratch and stain resistance
- Lowers the ongoing cost of floor care with less required labor compared to many conventional floor care methods
- Excellent ongoing, simplistic refreshability is possible with NeverStrip cleaners and pads
- Multi-year performance between reapplications is common

Surface Preparation

Completely remove any floor finish/acrylic/wax.

Clean the floor; remove dust and particulate matter.

Abrasion of the flooring surface is **not** needed to achieve a desired adhesion.

Application

Lightly shake prior to application (single component, no mixing, no pot life). If the surface is porous, apply 2-3 applications of NeverStrip Micron Primer (VCT) or Densi-Prime (Concrete/Stone) at 1,500 to 2,500 sq. feet per gallon per coat prior to applications of Micron All-Surface Sealer. A surface is considered porous if water readily penetrates and soaks into the substrate. Apply with a high quality, looped microfiber pad. Evenly dampen the microfiber pad with product (not soaked or dry). Apply Micron All-Surface Sealer as follows: Working in 3'X6' sections, squirt product onto the floor in a ribbon, across the middle width of the section to be coated and then spread the product evenly. Allow for a 10-minute dry time between applications. Allow 30 minutes before burnishing final application.

Micron All-Surface Sealer is applied thinner than conventional floor finish. Product dries rapidly. The microfiber pad should glide easily across the floor. The microfiber pad should not drag! A microfiber pad that drags may introduce streaking or a less desired appearance. Coverage per coat per gallon depends on factors including: 1) porosity of the floor, and 2) the person applying the product. Micron All-Surface Sealer naturally provides a medium or satin sheen. Burnishing after the final application will enhance the sheen. A higher speed burnisher will produce more gloss. A propane burnisher can be used for best results. Buffing Vinyl Seal with a 175-rpm floor machine will enhance the sheen but not as much as a higher speed burnisher. NeverStrip Micron Burnish Pad (8000 grit) is recommended for optimal shine.

Do not overapply the product! Do not overwork the product!

Application continues on next page

NeverStrip Micron All-Surface Sealer

Click <https://www.youtube.com/shorts/HXXB5RI93kU> or scan the QR Code to view a popular application technique using an application tool widely available.



Two to three applications of Micron All-Surface Sealer is typical at 5,000-6,000 SF/gallon/application or 1,250 to 1,500 SF/quart/application.

More Micron thin applications are best versus fewer heavy applications. Keep water off the floor after application for a minimum of 8 hours

Caution

Do not overapply the sealer ("Thin to win").

Do not overwork the sealer (This will cause streaking).

Do not use cleaners containing **Butyl**, **Citrus** or **Di-limonene**.

NeverStrip strongly recommends the use of our cleaner, **Micron Clean**, on a daily basis and our restorative cleaner, **Micron Restore**, on a periodic basis. Also, please ask about our **Micron Daily Clean & Buff Pad**.

Read and follow Product Data and Safety Data Sheets carefully.

Keep water off of the floor for 8 hours after application.

Removal

Micron All-Surface Sealer does not need to be removed/stripped in its normal lifecycle.

Removal can be accomplished using a high quality floor finish stripper with longer than typical dry times (50 minutes vs. 10 minutes) or by abrading the product off of the floor.

Cleaning & Maintenance

Click www.neverstrip.com/cleaning-maintenance or scan the QR code.



Packaging

- Sample, 8 oz. plastic bottle
- Quart, 32 oz. plastic bottle
- Gallon, 128 oz. plastic bottle

Coverage

5,000-6,000 SF/gallon/application or 1,250 to 1,500 SF/quart/application



NeverStrip Floor Coatings
2816 Centre Circle
Downers Grove, IL 60515
Info@neverstrip.com