

Category: Micron

System: Micron Tile Clean & Seal

Products: NeverStrip Tile Seal™

Surfaces: Ceramic, Porcelain, Quarry Tile



- 1) Thoroughly strip and clean the substrate, so it is free of all wax, sealers, soil and greases.
- 2) Apply 1st coat of Tile Seal™ using a pump-up sprayer or with looped micro fiber pad. Tile Seal™ should be spread thinly and evenly to completely cover the substrate. Spread at a rate of 4,000 to 6,000 SF per gallon. Remember, “Thin to Win” with Micron Films. Allow 5 to 15 minutes to dry.
- 3) Apply 2nd and 3rd coat of Tile Seal™ at 4,000 to 6,000 SF per gallon. This process will build a stain resistant microfilm over the entire floor.
- 4) Burnishing is optional. Use 3M Aqua (3100) burnishing pad.
- 5) Clean daily or as needed with NeverStrip Micron Clean™ at 1 oz. per gallon of water.
- 6) Once a month or as needed, clean with NeverStrip Micron Restore™, a cleaner/restorer product, preferably with an auto scrubber or floor machine with a red scrubbing pad. Use 4 – 12 oz. per gallon of water.

PLEASE NOTE: It can also assist to scrub floor with Micron Restore™ in an auto scrubber the first week, to reduce marks/scuffs on floor.

IMPORTANT:

- Additional instructions on Product Data Sheets and other resources are available at www.neverstrip.com.



21st Century Floor Care Technology™

neverstrip.com