

NeverStrip Coatings Remover™

NeverStrip Coatings Remover is used to remove or strip high performance coatings from hard surface flooring. This product is specifically formulated to remove difficult to remove coatings. **This product should not be used on resilient flooring.**

Characteristics

- Recommended for removal on brick, mortar, masonry, concrete, stucco, landscaping pavers, terrazzo, natural stone including marble, sand stone, and ceramic, porcelain, glazed tile and grout.
- Low odor with minimum or no ventilation requirement both indoor and outside.
- Nonflammable, noncombustible with minimal fire hazard.
- Effective in a wide temperature range of 32°F to 90°F.
- VOC: 50 grams per liter
- Coverage is typically 100 to 150 sq. feet per gallon.
- Store between 40°F and 130°F. If frozen, thaw and remix before using.

Packaging

- 16 oz.
- 1 Gallon
- 5-Gallon



800.854.5414
orders@neverstrip.com
www.neverstrip.com

For Hazardous Materials (or Dangerous Goods) Incident:
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC, Day or Night USA and Canada
800.424.9300

Surface Preparation

Surface should be clean and free from greases, oils, floor finishes and other contaminants. Surface must be dry at application.

Application

- 1 Wear protective eye wear and clothing
- 2 Stir before use
- 3 Apply directly by brush or roller
- 4 Allow to penetrate for 1-5 hours (longer in colder temperatures)
- 5 Use power washer with 15 tip or rinse and reclaim equipment with at 1,000 to 3,000 PSI maximum pressure. For optimum performance and speed of removal, use hot water at 190°F.
- 6 Excellent results may be obtained with a cold-water with the above specifications by doubling the dwell time.
- 7 Alternate method: after desired dwell time, agitate with a stiff nylon brush with a 175-rpm floor machine and remove with a quality wet vac or other extraction method including a high pressure rinse and reclaim system.
- 8 Clean up equipment after each use with water. Properly dispose of stripped coating and remover following all governmental regulations.

Caution

Always wear protective eye wear and chemical resistant gloves. Product can cause burns.

Protect all skin areas with chemical resistant covering.

If product gets on skin, wash off immediately. If product gets in eyes, flush with water for 15 minutes.

For Professional Use Only