

Micron Sealers Cleaning & Maintenance

NeverStrip Micron Sealers are:

- Liquid Grip for high traction on wet floors.
- Rubber Seal for most Rubber flooring surfaces
- Stone, Terrazzo and Concrete Seal for natural stone, terrazzo and concrete
- Tile Seal for Ceramic, Porcelain, Quarry Tile, Brick and Pavers
- Vinyl Seal for resilient flooring including: VCT, LVT, Linoleum, Sheet Vinyl, etc.

Core Cleaning & Maintenance Procedures (substitute equivalent pads & cleaners):

- Clean frequently with NeverStrip Micron Clean (1 oz./gal. of water).
- Use NeverStrip supplied microfiber pads to replace conventional mops & buckets.
- Use NeverStrip Red or Blue Scrubbing Pad with floor cleaning machines.
- Use NeverStrip Micron Pre-Treat for removal of stubborn marks & scuffs
- Use NeverStrip Doodlebug Pads, if needed, to remove marks & scuffs
- Burnish with NeverStrip Aqua Burnishing or Diamond Shine Pad.
- Periodically clean with NeverStrip Micron Restore (6 oz./gallon of water).
- Spot repair Micron Sealer as needed without repairing an entire room.
- Use the NeverStrip Micron Conditioning Pad or Diamond Pad to remove scuffs, marks, and surface scratching Micron Sealer prior to reapplication. Then, apply an application or two of Micron Sealer.
- There is seldom a need to remove or strip the Micron Sealer; however, the Sealer is removable from resilient and non-resilient flooring.

The procedures used and their frequency are a function of many factors, including traffic levels, soil load, cleaning effectiveness, and desired appearance.

Do:

- ✓ Follow NeverStrip's recommended floor care procedures;
- ✓ Clean spills quickly;
- ✓ Keep water off the floor for 8 hours after Sealer application;
- ✓ Scrub the floor and/or burnish (for higher shine) 5-7 days after Sealer application;
- ✓ Use NeverStrip Microbot Grease Eliminator to remove oils/greases;
- ✓ Use NeverStrip Micron Clean for daily/frequent cleaning (1 oz./gallon of water);
- ✓ Use NeverStrip Pre-Treat to remove stubborn marks and scuffs;
- ✓ Use NeverStrip Micron Restore for periodic cleaning (6 oz./gallon of water);
- ✓ Use NeverStrip supplied pads to maintain the Sealer
- ✓ Use soft brushes to clean NeverStrip Liquid Grip;
- ✓ Use Betco's Rip Saw or Juggernaut to chemically remove Micron Sealers from resilient flooring;
- ✓ Use diamond abrasives to remove Micron Sealers from stone, terrazzo and concrete;
- ✓ Use NeverStrip Floor Protectors on moveable furniture to prevent scratching;
- ✓ Use proper matting to reduce soil load from the outside;
- ✓ Use catch trays or place alcohol hand sanitizer dispensers over counters;
- ✓ Spot repairs as desired.

Do Not:

- ✗ Use traditional string mops to clean Micron Sealers;
- ✗ Use cleaners with d-limonene or any citrus cleaners;
- ✗ Use rubber mats, which get saturated with water or urine;
- ✗ Use Magic Eraser or equivalent material;
- ✗ Use acid-based toilet and urinal cleaners;
- ✗ Use pads to clean NeverStrip Liquid Grip;
- ✗ Apply tape onto Micron Sealers without first verifying compatibility;
- ✗ Allow water to puddle on Micron Sealers for an extended time (hours & hours). Drains must work, such as in showers.