



RS


RANDOM SIDEDRIVE

The BestPack™ RS Series is a Semi-Automatic Random Tape Carton Sealer built for speed and rugged dependability. Using side belt drives, the RS easily seals a wide range of random carton weights and sizes, with masts that allow for an extra 4" of carton height on the upper assembly. Able to effectively seal very light to very heavy cartons, BestPack's RS sealer is a workhorse and the most flexible unit in our random carton sealer product line.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



OPERATOR REQUIRED



RANDOM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements

UP TO 15 CPM

Speed


55-80 PSI, 5 SCFM

Air Requirements

410-600 LBS

Shipping Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.)
(4.25" - 20.0")

Height (min. - max.)
(4.0" - 21.0")

Specifications based on RS22-2

STANDARD FEATURES

- Adjustable Bed Height from:
RS22, RS23, & RS32: 20.5" - 30"
RS33: 20.5" - 30"
- 2 Side Belt Drive
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- UL Approved Electrical Parts
- Capable of Interchanging 2" or 3" Tape Heads
- Electrical On/Off Box can be Mounted on Either Side of the Carton Sealer
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm

OPTIONS

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Locking Heavy-Duty Casters
- Interlock Safety Gates
- Low Tape or No Tape Sensor
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Food Grade 304 Stainless Steel

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



SHORT OR LONG INFEEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short or 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine
Minimize downtime with BestPack's Spare Parts Kit.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

POPULAR RS MODELS

Please refer to comparison chart for complete list of models.

| MODEL | MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT | CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.) | CONVEYOR HEIGHT HEIGHT (min. - max.) | CARTONS PER MIN. | SHIPPING WEIGHT (LBS) |
|------------------------|---|--|---|------------------|-----------------------|
| RS22-2 2" Tape Head | (42.9") x (34.8") x (71.8") | (6.0" - U) x (4.25" - 20.0") x (4.0" - 21.0") | (20.5" - 30.0") | Up to 15 | 410 |
| RS22-3 3" Tape Head | (42.9") x (34.8") x (71.8") | (6.0" - U) x (5.25" - 21.0") x (4.0" - 21.0") | (20.5" - 30.0") | Up to 15 | 410 |
| RS23-2 2" Tape Head | (42.9") x (34.8") x (76.0") | (6.0" - U) x (4.5" - 20.0") x (4.0" - 30.0") | (20.5" - 30.0") | Up to 12 | 440 |
| RS23-3 3" Tape Head | (42.9") x (34.8") x (76.0") | (6.0" - U) x (5.5" - 21.0") x (4.0" - 30.0") | (20.5" - 30.0") | Up to 12 | 440 |
| RS32-2 2" Tape Head | (42.9") x (44.2") x (71.8") | (6.0" - U) x (4.5" - 30.0") x (4.0" - 20.5") | (20.5" - 30.0") | Up to 12 | 462 |
| RS32-3 3" Tape Head | (42.9") x (44.2") x (71.8") | (6.0" - U) x (5.5" - 30.0") x (4.0" - 20.5") | (20.5" - 30.0") | Up to 12 | 462 |
| RS33-3 3" Tape Head | (42.9") x (44.2") x (76.0") | (6.0" - U) x (5.5" - 30.0") x (4.0" - 30.0") | (20.5" - 30.0") | Up to 12 | 600 |

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
All Models Available in High Speed



For more information please go to:
WWW.BESTPACK.COM or call us at **1.888.588.2378**

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.