



ESHB

AUTOMATIC STRAIGHT FEED SUCTION CUP CASE ERECTOR

Our BestPack[™] Packaging ESHB is an innovative high performance carton erector/sealer using a bottom carton pull system in the hopper. The ESHB is designed for RSC cartons where both L x W have the same measurements (square cartons) and also standard rectangular cartons. The ESHB erector is built for heavy usage with quick and simple carton size change over. If you are looking for a simple yet heavy built carton erector, this is a must-see unit.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.







BOTTOM SEAL ONLY


2,425 LBS

Shipping

Weight

110 V 60 HZ Single Phase Current Power Requirements

CARTON RANGE



Length (min. - max.) (6.0" - 25.5")

Width (min. - max.) (6.0" - 14.0")

Height (min. - max.)

(6.5" - 20.0")

Specifications based on ESHB11-2

EXPERIENCE •

WWW.BESTPACK.COM

UP TO 10 CPM

Speed

100 PSI, 10+ SCFM Air

Requirements

STANDARD FEATURES

- Heavy Duty 3mm CNC Cut and Welded Frame Including Upper Welded Legs
- Carton Straight Fed from the Hopper / Carton **Bottom Pulled**
- Manual Jog Button for Step-by-Step Activation of All Movements to Confirm Proper Size Changes
- Quick Easy Manual Length, Width and Height Adjustments
- Tape Head Side Seal Adjustment
- Venturi Suction Cup System

C

- Hopper holds 70-100 Cartons Depending on the Carton
- Output: Up to 15 Cartons per Min. Depending on Carton Sizes and Ranges
- Variable Speed

OPTIONS

- Spare Parts Kit
- Allen Bradley PLC with Ethernet Capability
- Automatic Tape Head Center Seal Adjustment

- Allen-Bradley PLC Logic
 - Heavy Duty Maintenance Free Oil-less
- Air Cylinder Interlock Safety Gates Where Needed
- Alarm System for Low Tape/No Tape on
- Carton/No Cut Sensors with Malfunction Jam Detection and Three-colored Warning Light Carton on Demand Logic with Photo Eye
- Capable of Interchanging 2" or 3" BestPack Pop-out High Speed Tape Heads
- Carton is Righted as the Carton Leaves the Erector and Drops
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm

COMMUNIT

• Food Grade 304 Stainless Steel

Exit Conveyor

VERSION 4.5_1222

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT *Spare Parts Kits may vary based on machine* Minimize downtime with BestPack's Spare Parts Kit.



FOOD GRADE 304 STAINLESS STEEL This machine is available in 304 stainless steel which is food grade safe for food applications.



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

POPULAR ESHB MODELS

Please refer to comparison chart for complete list of models.

| MODEL | MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT | CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.) | CONVEYOR HEIGHT HEIGHT (min max.) | CARTONS PER MIN. | SHIPPING WEIGHT (LBS) |
|---------------------------------|---|---|--------------------------------------|---------------------|--------------------------|
| ESHB11-2 2" Tape Head | (126.0") x (75.0") x (79.0") | (6.0" - 25.5") × (6.0" - 14.0") × (6.5" - 20.0") | (22.5" - 30.0") | Up to 10 | 2,425 |
| ESHB11-3 3" Tape Head | (126.0") × (75.0") × (79.0") | (6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0") | (22.5" - 30.0") | Up to 10 | 2,425 |

Information subject to change without notice.

All Models Available in High Speed & Food Grade 304 Stainless Steel



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378**

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.