



# **ELVS**

### **AUTOMATIC L-TYPE SUCTION CUP CARTON ERECTOR**

The BestPack™ Model ELVS is an innovative, high-performance carton erector/sealer. This erector is built for heavy usage with quick and simple carton size changeover. There are no tools required for carton size changeover. The ELVS handles a wide range of carton sizes.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.







FULLY AUTOMATIC

UNIFORM CARTONS BOTTOM SEAL ONLY

110 VOLTS 60 HZ

Power Requirements **UP TO 10-15 CPM** 


Speed

**80 PSI, 10 SCFM** 

Air Requirements 1,800 LBS

Shipping Weight

## **CARTON RANGE**



Length (min. - max.) (8.0" - 25.0")

Width (min. - max.) **(5.0" - 20.0")** 

Height (min. - max.) (3.0" - 21.5")

Specifications based on ELVSL22-2H

## STANDARD FEATURES

- Heavy Duty 3mm CNC Cut and Welded Frame Including Upper Welded Legs
- · Quick and Easy Changeover
- Size Adjustment Screw Drive Counter for the Hopper Height Position and Carton Width
- Size Adjustment Screw Drive Counter for the Carton Length
- Power Feed Hopper
- Hopper Length of 40" for Carton Capacity
- Side Belt Drive with High Speed Motors
- Capable of Interchanging 2" or 3" BestPack Pop-out High Speed Tape Head
- Low Tape/No Tape on Carton/No Cut Sensors with Malfunction Alarm with Three-colored Light

- Manual Jog Button for Step-by-step Activation of All Movements
- Heavy Duty Maintenance Free Oil-less Air Cylinder
- Vacuum Pump Suction Cup System
- Allen-Bradley PLC Logic
- Carton on Demand Logic
- Heavy-duty Peg Legs
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm
- Free online install and maintenance videos

### **OPTIONS**

- Spare Parts Kit
- Allen Bradley PLC with Ethernet Capability
- Exit Conveyor
- Food Grade 304 Stainless Steel

WWW.BESTPACK.COM VERSION 4.7\_0822

## **EXTRA ACCESSORIES TO IMPROVE EFFICIENCY**



Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



### LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



e Parts Kits may vary based on machine\* Minimize downtime with BestPack's Spare Parts Kit.



### **FOOD GRADE 304 STAINLESS STEEL**

This machine is available in 304 stainless steel which is food grade safe for food applications.



### **CARTON SEALING TAPE**

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

## **POPULAR ELVS MODELS**

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
ELVSL21-2 2" Tape Head	(100.8") × (83.0") × (64.3")	(8.0" - 20.0") x (5.0" - 14.5") x (3.0" - 14.0")	(25.5" - 31.5")	Up to 10-15	1,800
ELVSL22-2H <b>2" Tape Head</b>	(100.8") × (83.0") × (64.3")	(8.0" - 25.0") x (5.0" - 20.0") x (3.0" - 21.5")	(25.5" - 31.5")	Up to 10-15	1,800
ELVSR22-2H 2" Tape Head	(100.8") x (83.0") x (64.3")	(8.0" - 25.0") x (5.0" - 20.0") x (3.0" - 21.5")	(25.5" - 31.5")	Up to 10-15	1,800
ELVSL22-3H <b>3" Tape Head</b>	(100.8") × (83.0") × (64.3")	(8.0" - 25.0") x (5.0" - 20.5") x (3.0" - 21.5")	(25.5" - 31.5")	Up to 10-15	1,800
ELVSR22-3H <b>3" Tape Head</b>	(100.8") x (83.0") x (64.3")	(8.0" - 25.0") x (5.0" - 20.5") x (3.0" - 21.5")	(25.5" - 31.5")	Up to 10-15	1,800

Information subject to change without notice.

All Models Available in Food Grade 304 Stainless Steel.

