

Color Selection Guide









30 Year Architectural Coatings

larson® by Alucoil® ACM is coil coated utilizing DURANAR® coatings from PPG. Backed by a 30-year exterior performance warranty, these (PVDF) fluoropolymer paint finishes contain 70% KYNAR® 500/ Hylar® 5000 resins and are formulated to meet or exceed industry performance requisites such as AAMA 620 and AAMA 2605. Our 29 standard colors are matched to a combination of popular ACM and steel foam panel colors - enabling greater flexibility and design choice.

wide flat sheets are available in select standard

availability.

colors. Please consult for finished goods inventory

Solid Color Series

These Duranar® 2-coat colors consist of a 0.2 mil primer and a 0.8 mil color coat, for a nominal dry film thickness of 1.0 mil.



Marakesh Red S-48

Deep Sea Blue S-74

Mica Color Series

These Duranar® 2-coat mica colors consist of a 0.2 mil primer and a 0.8 mil color coat, for a nominal dry film thickness of 1.0 mil. Mica flakes are suspended in the color coat – giving the appearance of a metallic finish.



Metallic Color XL Series

These Duranar® 3-coat metallic colors consist of a 0.2 mil primer, a 0.8 mil color coat, and a 0.5 mil clear coat, for a nominal dry film thickness of 1.5 mils.



Mica and Metallic XL Colors are directional in nature therefore proper estimating and installation precautions should be taken to ensure that panels are all installed in the same direction. Directional arrows are printed on panel protective film to aid in this practice.

Due to the reflectivity of these finishes, optical perception of color tone may vary according to the angle from which panels are viewed, reflected light off of other structures, and different angles or planes on which panels are installed on a building elevation.

To ensure color consistency with these finishes, it is highly recommended to order all material required at the same time, be they in single or multiple widths.

