

TOSHIBA

e-STUDIO™ 2510AC series

- > Color Multifunction Printer
- > Up to 25 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Customizable UI



e-STUDIO™ 2010Ac/2510Ac

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/LED Printing/ Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	20/25 PPM (LT)
First Copy Out	Color: 9.5/9.5 Seconds Monochrome: 7.1/7.1 Seconds
Warm-Up Time	Approx. 21 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	ST-R to LD, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 350 Sheets/Max. 2,900 Sheets
Original Feed	Optional 100-Sheet RADF
Scan Speed & Weights	RADF Scan: Up to 73 IPM (Monochrome or Color), Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond
Max. Original Size	LD
Paper Feed Sizes	Drawer 1: 250 Sheets-ST-R to LD Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to LD Opt. Paper Feed Unit: 550 Sheets-ST-R to LD Opt. 550-Sheet Paper Feed Pedestal-ST-R to LD Opt. 550-Sheet Drawer for PFP-ST-R to LD Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 250 Sheets-16 lb Bond-90 lb Index Stack Feed Bypass: 100 Sheets-16 lb Bond-110 lb Index Opt. Paper Feed Unit: 550 Sheets-16 lb Bond-90 lb Index Opt. 550-Sheet Paper Feed Pedestal: 16 lb Bond-90 lb Index Opt. 550-Sheet Drawer for PFP: 16 lb Bond-90 lb Index Opt. Envelope Cassette for PFP: 16 lb Bond-90 lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type): 17-28 lb Bond Standard Automatic Duplex Unit: 16 lb Bond-90 lb Index
Paper Weights	
Duplex	
Reproduction Ratio	25% to 400%
Max Duty Cycle	Max. 67.2K Month (e-STUDIO 2010Ac) Max. 84K Month (e-STUDIO 2510Ac)
Weight	Approx. 126 lb
Approx. Dimensions	22.6" (W) x 23" (D) x 31" (H)
CMYK Toner Yield	CMY: 33.6K, BK: 38.4K @ 5%
Power Source	120 Volts, 50/60 Hz, 12 Amps
Power Consumption	Maximum 1.5kW (120V)
CPU	Intel Atom™ 1.33GHz (Dual-Core)
Memory	2GB, Max. 4GB
Hard Disk Drive	320GB Self-Encrypting Drive

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	20/25 Pages Per Minute (LT)
Print Resolution	600 x 600 dpi (5 bit) 600 x 1,200 dpi (1 bit) PS3 Only
Operating Systems	Windows® 8.1.10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 11.4), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh® Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit), macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 11.4
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed), Optional 802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess, EFMS 6.30 (e-BRIDGE Fleet Management Software)
Account Control	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/ Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts

Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, NFC Authentication
*Conformance with HCD-PPv1.0 in High Security Mode.
ENERGY STAR® (V3.0), EPEAT Gold
WHQL (Windows® 8.1, 10, 2008 R2, 2012, 2012 R2, 2016, 2019), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Stds. Certification

Scan Specifications

Scan Speed	RADF Scan: Up to 73 IPM (Monochrome or Color)
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale 600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
Scan Resolution	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
File Formats	
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations /Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options			
RADF	MR3031	Card Reader Holder	GR1320
Platen Cover	KA5005PC	4GB Memory Option	GC1410
		FIPS HDD	GE1230
Additional Paper Options		Meta Scan Enabler	GS1010
Paper Feed Pedestal	KD1058	IPsec Enabler	GP1080
Paper Feed Unit	MY1047	Unicode Font Enabler	GS1007
Drawer Module	MY1048	Embedded OCR Enabler	
Envelope Cassette Option	MY1049	Per Seat License	GS1080NODE
Large Capacity Feeder	KD1059LB	Multi-Station Print Enabler	
		Per Seat License	GS1090NODE
Finishing Options		e-BRIDGE Plus for OneDrive for Business V3.0	GB2300NODE
Inner Finisher	MJ1042B	e-BRIDGE Plus for Sharepoint Online V3.0	GB2310NODE
Saddle-Stitch Finisher	MJ1110B	e-BRIDGE Plus for Exchange Online V3.0	GB2320NODE
Hole Punch Unit (For MJ1042)	MJ6011	External Interface Enabler	GS1020
Hole Punch Unit (For MJ1110)	MJ6105		
Bridge Kit	KN5005		
Job Separator	MJ5014		
Connectivity/Security Options		Miscellaneous Options	
FAX Unit/2nd Line for FAX Unit	GD1370N	Stand	STAND5005
FAX Over IP License Key	GS1100NODE	Accessible Arm	KK2550
Wireless LAN/Bluetooth	GN4020	Work Tray	KK5005
Bluetooth Keyboard	GR9000	Manual Pocket	KK5008
Accessory Tray	GR1330	Harness Kit for Coin Controller	GQ1280
Panel 10-Key Option	GR1340		



Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Web Site

www.business.toshiba.com