

PT-68 HEAVY DUTY POWER LIFTER



12" W x 24" H Small Steel Silhouette
(27 lbs.)



Manikin Mike™ 3DHT



Optional mounts available for a variety
of target configurations.

- Man portable, compact, weighs 32 lbs.
- Low profile footprint (16" x 24" x 30") for ease of relocation.
- Lifts up to 50 lbs. standard or 100 lbs. optional.
- Lifts rifle grade steel silhouettes, bullseye plates, and Manikin Mike™ 3DHTs within .2 seconds.
- Built in, unique self armoring design.
- Standard auto reset feature.
- Optional programmable electronic hit reactive target feature.

- Optional wireless, programmable (computer) control.
- Faster, more powerful, brawnier, "badder", better than LaRue targets.
- LOW PRICE, a COTS product, under GSA contract.

**Built in handles
for easy transporting**



PT-51

"DUMMY DUMPER" REACTIVE TARGET

With Electronic Sensored Manikin Mike™ (Mary) 3DHTs Targets

- Man portable, waterproof, temperature insensitive, heavy duty.
- No external controls required for operation.
- Built in programmable hit counting system, featuring thin film hit sensors.
- Life like 3D human targets, collapse after being hit by the appropriate number of rounds in the "kill zone".

PT-61 THE PORTABLE TACTICAL TARGET WITH A NEW TWIST!™



PT-61A

PT-61B

3 Wireless Target Control Options:
150 meters, 600 meters, and
up to 2,000 meters.

- Each target pops up, swivels, twists and/or rotates 0°, 90°, or 180° in a SINGLE target cycle.
- Unique BI-DIRECTIONAL target configuration built into a high speed pop up target mechanism.
- With BI-DIRECTIONAL target motion, TWO target images ("Shoot - Don't Shoot") can be presented during a SINGLE target exposure.
- Housed in a rugged, compact, very low profile, waterproof, all weather cast aluminum enclosure.
- Very portable; each target weighs less than 45 lbs. (including power supply).
- "Plug in and play" design for quick set-ups, relocations, and existing in-field expansions.
- Hardwired AC or wireless DC powered models available.
- Environmentally friendly; UV resistant; operating temperature range: -20° C to 80° C.
- Control up to 200 individual targets, at distances up to 2000 meters away.
- Thin film electronic hit sensing.
- Programmable electronic hit counting.
- Remote retrieval of individual target hit scores.
- Built in solid state rechargeable power supply.
- Built in pressure vent for humidity control.
- Low profile dimensions: 6" x 10.5" x 13"
- High speed operation. Time to raise, twist & face in full vertical position .4 seconds. Time to rotate 90° (edge-face) .1 second.
- Two accessory ports for multiple target enhancements.
- Stackable.
- Ideal for LIVE FIRE tactical training in MOUT, Hogan's Alleys, convoy protection, jungle walks, and building clearing exercises.
- COTS product; under GSA Contract GS 02F 0404D.

For More Information:

ADVANCED TRAINING SYSTEMS

4524 Highway 61 North • St. Paul, MN 55110 USA

Tel: 651.429.8091 • Fax: 651.429.8702

Email: info@atsusa.biz • Web: www.atsusa.biz

